



NOTES :

1. MATERIAL:

HOUSING-PBT POLYESTER UL94V-0
MIXED GLASS FIBER.

STANDARD COLOR-BLACK

CONTACTS-0.45mm DIAMETER PHOS-BRONZE
PLATED WITH GOLD FLASH.

2. CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.

3. UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]
.X ±0.30[0.012]

RoHS Compliant

| | | | |
|---|--|---|--|
| X MULTIPLE | | CONNECTING THE INFORMATION AGE | |
| XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chu, Taipei, Taiwan 11475 | | XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065 | |
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | G/ND: | |
| TITLE: RJ11 Connectors, W/D LED, 6P,2C, Unshielded, Thru-Hole | | DWG NO: XRJK-U-01-6-2-0-915 | |
| PART NO: XRJK-U-01-6-2-0-915 | | DRAWN: AUSTIN | |
| | | CHKD: JEFF | |
| | | DATE: Jan.09,06 | |
| UNIT: mm[inch] | | SHEET: 1 of 1 | |
| | | REV: 01 | |