



Notes:

- 1.Material:
Housing:High Themoplastic, UL 94 V-0, Black.
Terminal:Phosphor Bronze.
Cover:Brass.
- 2.Finish:
Terminal:Underplate:50u" Nickel, Contact area 10u" Au plated.
Soldertail:100u" Tin/Lead.
Cover:Underplate:50u" Nickel.
Ped:Goldflash over Nickel plate.
- 3.UNSPECIFIED TOLERANCE: .XX ±0.25[0.010] .X ±0.30[0.012]

<h1 style="margin: 0;">X MULTIPLE</h1>		CONNECTING THE INFORMATION AGE
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475	XMULTIPLE USA 543 Country Club Drive #B 128 Simi Valley, CA 93065	CUSTOMER/NO:
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG NO: XSXC-0-42M4-K010-20
TITLE: SM+XD 2 In 1 For 1CAV, With Protection		DRAWN: TARA
PART NO: XSXC-0-42M4-K010-20		CHKD: JEFF
	DIMENSIONS mm[inch]	SHEET 1 of 1
	REV 01	DATE 14/10/04